



**Highlight  
Ceiling White  
A-6000**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Vinyl Acetate/ Acrylic	Flat	Up to 350 Sq Ft Per Gallon	Brush, Roller, Pad or Airless Spray	Clean Water	Warm Soapy Water	30 Minutes	4 Hours	5 - 8 Days
<b>PRODUCT NAME:</b> A-6000 Highlight Ceiling White		This premium quality ceiling white is designed to impart a white matte finish with excellent light reflectance. Splatter free formulation provides excellent block out hide. This product complies with LEED Green Building Rating System GS-11 for interior flat paints.						
<b>WHERE TO USE:</b>		Acoustic Tile Plaster Drywall Wood Metal	Product is designed for interior ceiling applications. The matte flat finish eliminates the low angular sheen often exhibited by regular flat wall paints.					
<b>Surface Preparation:</b>		<p>New Work: The surface to be coated must be clean and free of dust, grease, wax rust, oil and bleeding stains.</p> <p>Priming –</p> <p>Drywall – Self Priming, for best results use 4190 Latex Primer Sealer.</p> <p>Plaster – For best results use No. 50 Block Out, 2000 Sungard.</p> <p>Wood – Alkyd Primer Undercoat 37-11.</p> <p>Ferrous Metal – Rust inhibiting metal primer such as 35-111, 2090 or 925-147.</p> <p>Galvanized – acrylic primer 36-11 or 180-11.</p> <p>Masonry – Masonry Sealer 43-10, 48-11, Block Filler 946-11.</p> <p>Repaint Work: On previously painted surfaces in good repair, no priming is generally necessary. On glossy surfaces remove the sheen with sandpaper or steel wool. Patch holes or cracks with appropriate filler. Spot prime bare areas with areas with indicated primer. remove any oil, chalk, dirt, wax or dust prior to recoating. Any loose or flaking paint should be removed and the edges feather sanded to produce a smooth, uniform surface.</p>						
<b>Application:</b>		<p>Stir product thoroughly with a circular, lifting motion to disperse into a homogenous liquid.</p> <p>Roller – 3/8" to 1 1/4" nap, depending on surface texture.</p> <p>Brush – Nylon or polyester filament.</p> <p>Airless Spray – Tip size at atomization pressures will vary with type of equipment.</p> <p>Best results are more likely obtained by using quality application tools. Seal water stains or other bleeding stains with O'Leary Seal-It Stain Killer before paint application.</p>						
<b>NOTE: Formulated without mercury or lead.</b>								

<b>Resin:</b>	Vinyl Acetate/Acrylic Co-polymer
<b>Solids:</b>	Weight – 40.5% Volume – 28.6 %
<b>Weight Per Gallon:</b>	10.26 lbs.
<b>Viscosity:</b>	98 – 102 (Krebs Units)
<b>Specular Gloss:</b>	0 – 3% @ 85 degrees
<b>Recommended Film Thickness:</b>	Wet – 3.5 to 4.5 mils Dry – 1.7 to 2.5 mils
<b>VOC – VOS Statement:</b>	This product contains less than 0.42 lbs per gallon or 50 G.P.L.
<b>Cautions:</b>	<b>CAUTION!</b> Do not take internally. Close container after each use.  <b>KEEP OUT OF REACH OF CHILDREN.</b>

05/04/2018